DATA SHEET

Display E19-9

Issue: **September 2009**

All-round Display: 48.3 cm/19-inch TFT
Enter the world of LCD displays

The display E19-9 offers you all the benefits of LCD technology at a very competitive price.

Resolution 1280 x 1024 for perfect office experience

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

48.3 cm/ 19” display in optimum 5:4 standard format

Representative design with space saving front frame and smart details like discretely integrated speakers

RESPONSE TIME SPEAKER ENERGY STAR TCO'03 DISPLAYS

Display E19-9

Special features	
	Aspect ratio conversion, cable guide
Stand details	
Stand	removable
Tilt angle	-5° / +15°
Picture performance	
Contrast - advanced	3000:1
Response time black to black typical	5 ms
Viewing angle (h/v)	170° / 160°
Color performance	16.7 Mio colors (Hi-FRC)
Brightness - typical	300 cd/m²
Size and resolution	
Aspect ratio	5:4
Diagonal Size	48.3 cm (19-inch)
Resolution (native)	1280 x 1024 pixel (recommended)
Resolution (interpolated)	1280 x 768 pixel, 800 x 600 pixel
Picture size	376.3 x 301 mm
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	30 - 83 kHz
Vertical	56 - 75 Hz
Frequencies - bandwidth	165 Mhz
Connectivity	
Video input	1 x D-SUB, 1 x DVI
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack
OSD Languages and setting options	
Languages	Chinese, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish
Brightness / Contrast	Brightness, Contrast
Color	Cold, Warm, Custom Color
Image adjust	Clock, H-Position, V-Position, Expansion
Audio	Mute, Volume
Information	Resolution/mode, Signal input
Mode	General, Movie, Picture, Game
Power consumption (typical, w/o sound)	
Soft switch off	0.7 W
Power save mode	0.7 W
Operating with EPA settings	23 W
Operating maximum brightness	32 W
Electrical values	
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1
Compliance	
Europe	CE

Compliance	
USA/Canada	FCC Class B, cUL
Russia	GOST
Saudi Arabia	SASO
Global	ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability	
MTBF (demonstrated)	50000 h

Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	402.4 x 60.5 x 346.1 mm
Dimension with stand (W x D x H)	402.4 x 189 x 421.6 mm
Weight (packed)	5.16 kg
Weight (unpacked)	3.62 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous	
	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock

Package content	
	Data cable 1.8m, D-SUB (15-pin), Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, User manual, Warranty booklet

Order code	
SAP order name	Display E19-9
Order Code	S26361-K1340-V160
EAN-Nr.	4049699174704

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions September 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com